

WIDE-STEP PLATFORM

- INTEGRATED CLEATS FOR IMPROVED TRACTION AND SAFETY
- OSHA COMPLIANT 5.5" CLEAR STEP WIDTH AND BOOT STOP

FORGED STEEL ANCHOR BOLT

- EXCEEDS 3,200 LBS (LOAD@ YIELD 1" INSIDE BOOT STOP)
- FITS MINIMUM 1" DIAMETER HOLES ON ROUND STEEL OR COMPOSITE POLES
- DESIGNED FOR POLE WALL THICKNESS UP TO 1.57"

SECURE INSTALLATION

- POWDER COATED ALUMINUM STEP HOUSING FOR LONG TERM DURABILITY AND PROTECTION
- SUPPLIED WITH 2 HEAVY HEX NUTS AND WASHER FOR SECURE INSTALLATION
- TDG (THERMAL DIFFUSION GALVANIZING) HARDWARE FOR LONG TERM PROTECTION

MADE IN THE USA

- PATENTED.
- BOLT & HOUSING ARE LOT NUMBERED FOR TRACEABILITY

100% 
USA MADE & SOURCED MATERIALS

INTEGRATED FALL ARREST

- FALL ARREST (ANCHOR POINT) EXCEEDS 5,000 LBS REQUIREMENT

POLE STEP W/ FALL ARREST

3/4" L BOLT / ALUMINUM HOUSING

Designed for installation into a minimum 1" diameter hole on round steel or composite pole structures. Incorporates a fully forged 3/4" anchor bolt with a wide-step aluminum housing to improve climber comfort and safety. The anchor bolt is keyed to the housing to prevent rotation inside the pole and includes an integrated fall-arrest loop rated to exceed the 5,000 lbs.

| PART # | COLOR (STEP HOUSING) |
|----------|----------------------|
| APSF-02 | BROWN |
| APSF-02G | GRAY |